

QUALITY MANAGEMENT ISO 9001

Code: TD_EGGER_Skirtings_Decor_EN

Revision: 01

Date: 18.11.2020

Technical data sheet

EGGER Décor Skirtings

Material data

Parameter	Unit			
Surface		Melamin-/ urea impregnated decor paper		
Carrier material		MDF (medium density fibreboard)		
Product		Beading profile 1,6 cm with adhesive strip	Skirting 8 cm cubical	Skirting 6 cm
Profile drawing				
Length	mm	2400	2400	2400
Thickness	mm	16	14	17
Width	mm	16	80	60
Colour		see decor list skirting		
Paintable		No		
Skirting per package	piece	25	5	10
Meter per package	m	60	12	24
Skirting per pallet	piece	600	360	400
Meter per pallet	m	1440	864	960
Method of use		self-adhesive strip	adhesive (SMP construction adhesive or 1K PU adhesive) tacking (compressed-air tacker)	Clipstar (distance 25-50 cm depending on the wall construction)

Skirting (MDF)

Parameter	Skirting	Test method
Formaldehyde Emission	E 1	EN 120
VOC-and Formaldehyde emission	A+	ISO 16000 part 3,6, 9,10
Light resistance	level 7	EN 20105
Recycling	recyclable	
Disposal	in burning plant /incinevator	
Storage	Standing or lying on an even base. Protect it from direct sunlight and moisture Climatic conditions : tempature 18°C, humidity 55-70%	

The tolerance for cross section mass, longitudinal dimensions as well as distortion and bend corresponds RAL-RG 432.

We confirm that in the manufacturing process, in the semi-finished goods and in the skirting's itself no top coating, no paints, no lacquers and no adhesives with organic solvents, biocides and free formaldehyde are used and contained.